



BORE	SUC. 2 / DIS. 1-1/2
TOTAL HEAD	Ft
CAPACITY	GPM
MOTOR	3HP (2.2kw)
	Indoor use-outdoor use TYPE
	V 60Hz 2P 3φ
LIQUID	NAME
	CONC. % S. G.
	TEMP. °F

22	CUT SEAL	1	FPM	
21	HEX. BOLT	1	PVC	
20	BOLTS	4	SUS	
19	SHAFT CRAMP COLLARS	2	S35C	
18	O-RINGS	2	EPDM-FPM	
17	SEAL CASE	1	CFR PP/CERAMICS	
16	MOTOR BASE	1	PP	
15	O-RING	1	EPDM	
14	DRY SEAL	1	FPM	
13	IMPELLER	1	CFR PP/C3604B	
12	IMPELLER KEY	1	SUS 316	
11	O-RING	1	EPDM-FPM	
10	IMPELLER NUT	1	CFR PP	
9	HEX. BOLTS with NUTS	8	SUS-TITANIUM	
8	O-RING	1	EPDM-FPM	
7	PUMP CASING	1	CFR PP	
6	CONNECTING PIPE	1	CFR PP	
5	HEX. BOLTS	8	SUS	
4	PUMP SHAFT	1	SUS 304	
3	BASE	1	GFR PP	
2	HEX. BOLTS	4	SUS	
1	MOTOR	1		

No.	品名	PARTS NAME	数量	材質	MATERIAL	備考	NOTE
-----	----	------------	----	----	----------	----	------

名称 TITLE VERTICAL SEALLESS PUMP

型式 MODEL YD-42VK-BK36-JN

承認者 APPROVED BY	検閲者 CHECKED BY	設計・製図者 DRAWN BY	日付 DRAWN DATE
		M. HARIGAE	May. 01, 2002
変更者 ALTERATION	設計・製図者 DRAWN BY	日付 DRAWN DATE	

図面番号 Dwg.No. VM-3971-0

尺度 SCALE FREE

株式会社 ワールドケミカル
World Chemical Co., Ltd.

UNIT IN Inch (mm)