



MODEL	YD-50VP-BK36-JN YD-50VK-BK56-JN YD-50VP-BK56-JN
BORE	SUC. 2-1/2 / DIS. 2
TOTAL HEAD	Ft
CAPACITY	GPM
MOTOR	3HP (2.2kW) / 5HP (3.7kW)
	Indoor use-Outdoor use TYPE
	V 50-60Hz 2P 3φ
LIQUID	NAME
	CONC. % S.G.
	TEMP. °F

22	CUT SEAL	1	FPM	
21	HEX. BOLT	1	PVC	
20	BOLTS	4	SUS	
19	SHAFT CRAMP COLLARS	2	S35C	
18	O-RINGS	2	EPDM-FPM	
17	SEAL CASE	1	CFR PP/CERAMICS	
16	MOTOR BASE	1	PP	
15	O-RING	1	EPDM	
14	DRY SEAL	1	FPM	
13	IMPELLER	1	CFR PP/C3604B	
12	IMPELLER KEY	1	SUS 316	
11	O-RING	1	EPDM-FPM	
10	IMPELLER NUT	1	CFR PP	
9	HEX. BOLTS with NUTS	8	SUS-TITANIUM	
8	O-RING	1	EPDM-FPM	
7	PUMP CASING	1	CFR PP	
6	CONNECTING PIPE	1	CFR PP	
5	HEX. BOLTS	8	SUS	
4	PUMP SHAFT	1	SUS 304	
3	BASE	1	CFR PP	
2	HEX. BOLTS	4	SUS	
1	MOTOR	1		

No.	品名	PARTS NAME	数量	材質	MATERIAL	備考	NOTE
名称 TITLE VERTICAL SEALLESS PUMP							
型式 MODEL							
APPROVED BY	CHECKED BY	設計・製図	日付				
		M. HARI GAE	May. 01. 2002				
ALTERATION		設計・製図	日付				
△ X		DRAWN BY	DRAWN DATE				
図面番号 Dwg.No.	VM-3972-0			尺度 SCALE	FREE		
株式会社 ワールドケミカル World Chemical Co., Ltd.							

UNIT IN Inch (mm)