



MODEL	YD-65VK-BK106-JN YD-65VP-BK105-JN YD-65VP-BK106-JN
BORE	SUC. 3 / DIS. 2
TOTAL HEAD	Ft
CAPACITY	GPM
MOTOR	10HP (7.5Kw)
	Indoor use-Outdoor use TYPE
	V 50-60Hz 2P 3φ
LIQUID	NAME
	CONC. % S.G.
	TEMP. °F

22	CUT SEAL	1	FPM	
21	HEX. BOLT	1	PVC	
20	BOLTS	4	SUS	
19	SHAFT CRAMP COLLARS	2	S35C	
18	O-RINGS	2	EPDM-FPM	
17	SEAL CASE	1	CFR PP/CERAMICS	
16	MOTOR BASE	1	PP	
15	O-RING	1	EPDM	
14	DRY SEAL	1	FPM	
13	IMPELLER	1	CFR PP/C3604B	
12	IMPELLER KEY	1	SUS 316	
11	O-RING	1	EPDM-FPM	
10	IMPELLER NUT	1	CFR PP	
9	HEX. BOLTS with NUTS	8	SUS-TITANIUM	
8	O-RING	1	EPDM-FPM	
7	PUMP CASING	1	CFR PP	
6	CONNECTING PIPE	1	CFR PP	
5	HEX. BOLTS	8	SUS	
4	PUMP SHAFT	1	SUS 304	
3	BASE	1	GFR PP	
2	HEX. BOLTS	4	SUS	
1	MOTOR	1		

No.	品名	PARTS NAME	数量	材質	MATERIAL	備考	NOTE
名称		VERTICAL SEALLESS PUMP					
型式		MODEL					
承認	検閲	設計・製図	日付				
APPROVED BY	CHECKED BY	DRAWN BY	DRAWN DATE				
		M. HARI GAE	May. 01. 2002				
変更		設計・製図	日付				
ALTERATION		DRAWN BY	DRAWN DATE				
△ X							
図面番号	VM-3975-0					尺度	SCALE
Dwg.No.						FREE	
 株式会社 ワールドケミカル World Chemical Co., Ltd.							

UNIT IN Inch (mm)